

Technical Specifications

Model t237k	DN021A
Processor & Speed	2.4HT GHz/800 Intel® Pentium® 4 Processor – PGA478
Chipset	Intel® 865G
Motherboard	P4SD-LA-GL6E
RAM	256/3200 MB DDR SDRAM
Maximum	4 GB (4x1024MB DDR SDRAM)
Sockets	Four 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	Two
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	8KB Data Cache + Trace Cache L1, 512 KB L2 Integrated on Processor module
Hard Drive	80 GB (7200 RPM)
Optical Drive	CD-RW/DVD-ROM Drive 48x24x16x48 48X- Write /24X - Re-write /16x- DVD Read 48X - CD-ROM Read
Average Random Access	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Diskette Drive	None
6 in 1 Card Reader	Compact Flash I/II; Memory Stick; MMC/SD; Smart Media
Video Graphics	AGP 8X Graphics Card
Controller	nVidia GeForce4™ MX-440
Video Memory	64 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - NTSC
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
MPEG-1/2	MPEG-2 for full-screen, full-motion digital video
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Jaguar, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	6= USB, 1= serial, 1= parallel, 2=1394
Front I/O Connector	2= USB, 1= 1394; 6 in 1 Card Reader; 1= Microphone; 1= Line In; 1= Headphone
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	3= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2003
This information is subject to change without notice and
is provided "as is" with no warranty.

Hewlett-Packard shall not be liable for any direct,
indirect, special, incidental or consequential damages
in connection with the use of this material.